

CRT	Size (Diagonal: 17" (43.2cm), Pure Flat
Viewable Image Size	16.0" (40.6cm)
Pre-set Display Area	Default: 310mm x 230mm Overscan: 315mm x 236mm
Dot Pitch	(D) 0.25mm, (H) 0.21mm
Scan Frequency	Horizontal: 30K~72KHz Vertical: 50~160Hz
Pixel Frequency	110MHz
Compatibility	VESA, SXGA, XGA, SVGA, VGA
Signal Input	Video: 0.7Vp-p, RGB analog
Maximum Resolution	1280 x 1024 @ 60Hz
Factory Pre-set Mode	8
User Programmable	
Power Source	Universal 100~240 Vac, 50Hz / 60Hz
Power Consumption	75 Watts (Max.)
EPA ENERGY STAR ®	Yes
Video Signal Connectors	15-pin mini D-sub Male
Front Panel Controls	4 OSD Buttons ,Power On/Off
OSD Function	Brightness, Zoom, H-size, H-center, V-size, V-center, Pincushion, Trapezoid, Rotation, 6500K, 9300K, User's Color, Degauss, H/V Moiré Reduce, Recall, Language(English, German, French, Spanish, Italian), Exit
Base Operation	Tilt: -5°/+15° Swivel: -45° / +45°
Plug & Play	VESA DDC1/2B
Emissions Standard	MPRII
Regulations	UL, FCC, CSA, TUV / GS, CE
Other Features	n/a
Dimensions (WxHxD mm)	Monitor: 397x410x413; Carton: 460x460x515
Dimensions (WxHxD inches)	Monitor: 15.6x16.15x16.3; Carton: 18.12x18.12x20.3
Monitor Dimensions without Base	n/a
Weight	Net: 34.2lbs (15.5kg); Gross: 38.1lbs (17.3kg)
Loading Qty without Pallet	n/a
Loading Qty with Pallet	n/a
Warranty	3 Year Parts & Labor
UPC Code	663555007841